



Product Name	160A
Manufacturer	Schneider Electric
Category	Distribution Board

TECHNICAL SPECIFICATIONS


Electrical Specifications	
System Voltage	3Ph., 400V, 50Hz
Neutral/Earth System	Separate (TN-S)
Major Components	Schneider Electric
Auxiliary Supply Voltage	230V AC
Auxiliary Supply Origin	From incomer
Wiring	1.5 sqmm
Bus Bars (mm)	
Main (vertical)	20x5 mm
Neutral	20x5 mm
Earth	20x5 mm
Connections	
Inlet	1x160A Breaker
Outlets	1x125A 5pin, 2x63A 5pin, 3x32A 5pin, 3x32A 3pin
Termination	Direct to device Incoming
Through Socket	Outgoing
Cable Entry	Bottom Incoming / Outgoing


Distribution Board



Extras		
Enclosure	Canopy stand, weather proof	
Material	RAL 7032 sheet steel	
Degree of Protection	IP-55	
Mounting	Pedestal	
Presentation	Functional door	
Type of Construction	Form-2	

WEIGHTS & DIMENSIONS





Height (H) mm	Width (W) mm	Length (L) mm
850 mm	500 mm	250 mm

Weight (kg)	
Weight	30 kg

www.rentalgp.com

©2024 Glow Power Equipment Rental LLC

All rights reserved.

This publication is based on datasheets from respective manufacturers and is intended for informational purposes only. All trademarks and proprietary materials belong to their owners. Glow Power holds no rights to the technical data presented and does not intend to infringe upon copyrights or trademarks.