P50-3_50Hz

Diesel Generator





| Product Name | P50-3_50Hz |
|--------------|------------------|
| Manufacturer | FG Wilson |
| Category | Diesel Generator |

TECHNICAL SPECIFICATIONS

| Electrical Specifications | |
|---------------------------|---------------------|
| Rated Voltage (V) | 230-400 V |
| Frequency (Hz) | 50 Hz |
| Prime Power (kVA/kW) | 45 kVA / 36 kW |
| Standby Power (kVA/kW) | 36 kVA / 40 kW |
| Power Factor | 0.8 |
| Generator Specifications | |
| Engine Make/Model | Perkins 1103A-33TG1 |
| Number of Cylinders | 3 |
| Bore x Stroke (mm) | 105 x 127 mm |
| Fuel Type | Diesel |
| Oil Capacity (L) | 8.3 L |
| Radiator Air Flow, m³/min | 86.4 m³/min |
| Total Coolant Capacity, L | 10.2 L |
| Alternator | |
| Make/Model | FG Wilson FGL20060 |
| Number of Bearings | 1 |
| Over Speed, rpm | 2250 |
| Temperature Rise, °C | 50° C |

P50-3_50Hz


Diesel Generator




| Fuel Consumption | | |
|--------------------------|-----------------|--|
| Recommended Fuel | Class A2 Diesel | |
| Fuel tank capacity (L) | 145 L | |
| 100% load with fan, L/hr | 10.5 L/hr | |
| 75% load with fan, L/hr | 7.8 L/hr | |
| 50% load with fan, L/hr | 5.6 L/hr | |

| Modular Acoustic Enclosure | |
|---------------------------------|--------|
| Sound Pressure Level (dBA) @ 7m | 63 dBA |
| Enclosure Type | Canopy |

WEIGHTS & DIMENSIONS





| Length (L) mm | Width (W) mm | Height (H)mm |
|---------------|--------------|--------------|
| 2291 mm | 1026 mm | 1426 mm |

| Dry Weight (kg) | |
|-----------------------|---------|
| Open Type | 764 kg |
| Sound Attenuated Type | 1025 kg |

www.rentalgp.com

©2024 Glow Power Equipment Rental LLC

All rights reserved.

This publication is based on datasheets from respective manufacturers and is intended for informational purposes only. All trademarks and proprietary materials belong to their owners. Glow Power holds no rights to the technical data presented and does not intend to infringe upon copyrights or trademarks.