

# GLT6-A K3

## Tower Light



<b>Product Name</b>	<b>GLT6-A K3</b>
<b>Manufacturer</b>	Generac
<b>Category</b>	Tower Light

## TECHNICAL SPECIFICATIONS

Electric Specifications	
Mast lifting system	Hydraulic
Mast rotation	340°
Floodlights	6x 320W LED
Luminous flux	276000 Lm
Illuminated area (1 lux min)	12536 m <sup>2</sup>
Engine	Kubota D1105
Engine cooling	Liquid
Cylinders (q.ty)	3
Engine speed (50/60 Hz)	1500 / 1800 rpm
Alternator (50/60 Hz)	8kVA 230V / 8kVA 240V
Outlet socket (16A)	2
Inlet plug (16A)	1
Avg. sound pressure	63 dB(A) @ 7m
Tank capacity (gross/net)	200/180 l
Running time	140 h
Liquid containment (110%)	√
Wind speed resistance	110 km/h

# GLT6-A K3

## Tower Light



### WEIGHTS & DIMENSIONS

Length (L) mm	Width (W) mm	Height (H)mm
Min: 2156 mm	1400 mm	2403 mm
Max: 3095 mm	2166 mm	8387 mm

Dry Weight (kg)	
Weight	900 kg



[www.rentalgp.com](http://www.rentalgp.com)

©2024 Glow Power Equipment Rental LLC

All rights reserved.

This publication is based on datasheets from respective manufacturers and is intended for informational purposes only. All trademarks and proprietary materials belong to their owners. Glow Power holds no rights to the technical data presented and does not intend to infringe upon copyrights or trademarks.