

LINEAX 5G35

Power Cables



Product Name	LINEAX 5G35
Manufacturer	Nexans
Category	Power Cables

TECHNICAL SPECIFICATIONS

Construction characteristics

With Green/Yellow core	Yes
Conductor flexibility	Flexible class 5
Conductor material	Plain annealed copper
Conductor shape	Circular
Insulation	Cross-linked synthetic elastomer type EI 4
Lead free	Yes
Outer sheath	Cross-linked synthetic elastomer type EM 2
Sheath color	Black
With smaller neutral conductor	No

Dimensional characteristics

Number of cores	5
Conductor cross-section	35 mm ²
Maximum outer diameter	45.1 mm
Minimum outer diameter	35.8 mm
Approximate weight	2675 kg/km
Neutral conductor section (when smaller)	- mm ²

Mechanical characteristics

Mechanical resistance to impacts	Very good
Cable flexibility	Flexible

Electrical characteristics

Rated Voltage U ₀ /U (U _m)	450/750 V
Permissible current rating in open air	150 A
Voltage drops, single phase	- V/A.km

Usage characteristics

Packaging	Drum
Length	- m
Chemical resistance	Accidental
Waterproof	Good
Flame retardant	IEC 60332-1
Max. conductor temperature in service	85 °C
Minimum dynamic operating bending radius	270.6 mm
Minimum static operating bending radius	135.3 mm
Oil resistance	Yes
Operating temperature, range	-25 ... 55 °C
Short-circuit max. conductor temperature	200 °C
Weather resistance	Very good

www.rentalgp.com

©2024 Glow Power Equipment Rental LLC

All rights reserved.

This publication is based on datasheets from respective manufacturers and is intended for informational purposes only. All trademarks and proprietary materials belong to their owners. Glow Power holds no rights to the technical data presented and does not intend to infringe upon copyrights or trademarks.